

WALK-THROUGH SURVEY REPORT:
CONTROL TECHNOLOGY FOR MANUAL TRANSFER OF CHEMICAL POWDERS

AT

Colgate-Palmolive Company
Clarksville, Indiana

REPORT WRITTEN BY:
Frank W. Godbey

REPORT DATE:
July 1984

REPORT NO.:
149-21a

NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH
Division of Physical Sciences and Engineering
Engineering Control Technology Branch
4676 Columbia Parkway
Cincinnati, Ohio 45226

PLANT SURVEYED: Colgate-Palmolive Co.
State and Woerner Ave.
Clarksville, IN 47130

SIC CODE: 2844, 2841

SURVEY DATE: May 25, 1984

SURVEY CONDUCTED BY: Frank W. Godbey

EMPLOYER REPRESENTATIVES CONTACTED: Leslie L. Greathouse, Supervisor of
Safety & Labor Relations -
812/283-6611
Mike Hubbs, Plant Engineer
812/283-6611

EMPLOYEE REPRESENTATIVES CONTACTED: No Employee Representatives

I. INTRODUCTION

The National Institute for Occupational Safety and Health (NIOSH) is the primary Federal agency engaged in occupational safety and health research. Located in the Department of Health and Human Services (formerly DHEW), it was established by the Occupational Safety and Health Act of 1970. This legislation mandated NIOSH to conduct a number of research and education programs separate from the standard setting and enforcement functions carried out by the Occupational Safety and Health Administration (OSHA) in the Department of Labor. An important area of NIOSH research deals with methods for controlling occupational exposure to potential chemical and physical hazards. The Engineering Control Technology Branch (ECTB) of the Division of Physical Sciences and Engineering has been given the lead within NIOSH to study the engineering aspects of health hazard prevention and control.

Since 1976, ECTB has conducted a number of assessments of health hazard control technology on the basis of industry, common industrial process, or specific control techniques. Examples of these completed studies include the foundry industry; various chemical manufacturing or processing operations; spray painting; and the recirculation of exhaust air. The objective of each of these studies has been to document and evaluate effective control techniques for potential health hazards in the industry or process of interest, and to create a more general awareness of the need for or availability of an effective system of hazard control measures.

These studies involve a number of steps or phases. Initially, a series of walk-through surveys is conducted to select plants or processes with effective and potentially transferable control concepts or techniques. Next, in-depth surveys are conducted to determine both the control parameters and the effectiveness of these controls. The reports from these in-depth surveys are then used as a basis for preparing technical reports and journal articles on effective hazard control measures. Ultimately, the

information from these research activities builds the data base of publicly available information on hazard control techniques for use by health professionals who are responsible for preventing occupational illness and injury.

This plant was visited as part of a study of dust control during the manual handling of dry chemical powders and the manual transfer of those materials to some type of processing device, i.e., V-blender, Banbury mixer, etc. Ultimately, this project will result in a concise article describing dust control techniques during manual transfer of chemical powders.

II. PLANT AND PROCESS DESCRIPTION

PLANT DESCRIPTION

This facility consists of many multi-storied brick and concrete reinforced industrial buildings containing approximately 1.25 million square feet of floor space and situated on 53.8 areas of land. The plant employs 910 workers and operates three shifts per day, five days a week in the manufacture of laundry detergents, bar soap and toothpaste.

PROCESS DESCRIPTION

Raw materials for toothpaste, the major batching area, are transported to the area via forklift truck in palletized bags. The preweighed bag ingredients are dumped directly into various hoppers. Other ingredients are scooped from bags and dumped into the hoppers. The materials flow by gravity from the hoppers into mixers where they are mixed with liquids to produce the finished product. The finished product is conveyed to the filling lines where it is containerized, packaged and sent to storage for distribution.

POTENTIAL HAZARDS

The major ingredients in the manufacture of these products are sodium benzoate, monosodiumfluorophosphate, carboxymethylcellulose, phosphates and sodium sulfate.

III. CONTROLS

PRINCIPLES OF CONTROL

Occupational exposures can be controlled by the application of a number of well-known principles, including engineering measures, work practices, personal protection, and monitoring. These principles may be applied at or near the hazard source, to the general workplace environment, or at the point of occupational exposure to individuals. Controls applied at the source of the hazard, including engineering measures (material substitution, process/equipment modification, isolation or automation, local ventilation) and work practices, are generally the preferred and most effective means of control both in terms of occupational and environmental concerns. Controls which may be applied to hazards that have escaped into the workplace environment include dilution ventilation, dust suppression, and housekeeping. Control measures may also be applied near individual workers, including the use of remote control rooms, isolation booths, supplied-air cabs, work practices, and personal protective equipment.

In general, a system comprised of the above control measures is required to provide worker protection under normal operating conditions as well as under conditions of process upset, failure and/or maintenance. Process and workplace monitoring devices, personal exposure monitoring, and medical monitoring are important mechanisms for providing feedback concerning effectiveness of the controls in use. Ongoing monitoring and maintenance of controls to insure proper use and operating conditions, and the education and commitment of both workers and management to occupational health are also important ingredients of a complete, effective, and durable control system.

These principles of control apply to all situations, but their optimum application varies from case-to-case. The application of these principles are discussed below.

This toothpaste and laundry products manufacturing operation uses local and general exhaust ventilation to remove or dilute potential air contaminants generated during the processing of dry materials. The ventilation systems design appears to be based on the American Conference of Governmental Industrial Hygienist's Ventilation Manual.

WORK PRACTICES

Workers are encouraged to use good work practices. They are provided instruction when they start the job and receive updates and reinforcement as needed. Health and safety educational material and a health and safety committee are provided to encourage a sustained good work practices effort.

MONITORING

Employees are given preemployment physicals and periodic hearing tests for those working in noisy areas. There is a full-time nurse and a community physician is available. The health and safety committee meets monthly and inspects the plant. The company's staff performs periodic dust monitoring.

PERSONAL PROTECTION

Safety glasses, safety shoes, ear plugs, and respirators are provided on an "as-needed" basis.

IV. CONCLUSIONS AND RECOMMENDATIONS

This plant represents a general type of automated dry materials handling operation and does not have sufficiently unique manual batching controls to warrant performing an in-depth study. Therefore, an indepth survey is not recommended.

TO: Deborah Hamilton
FROM: Engineering Control Technology Branch
RE: Report No. 149-71a

The following are keywords for inclusion in DIDS:

Company Name: Colegate - Palmolive Company

Alternate Company Names: (such as parent company) None

SIC CODE: 2841, 2844

Process and/or Equipment Studied: Batching of chemical powders.

Materials Sampled For: None

Additional Keywords: Control Technology, manual transfer